



softena
POU
drinking
water
filter



softena
 A real sense
 of comfort &
 performance.

ERIE WATER TREATMENT
 Bannerlaan 83E,
 B-2280 Grobbendonk - Belgium
 T +32 (0)14 28 51 71
 infobelgium@eriewatertreatment.com
WWW.ERIE-IQSOFT.COM

MEMBERSHIPS



CERTIFICATIONS

TECHNICAL SPECIFICATIONS

| | |
|---|-----------------------|
| Operating pressure max (bar) | 6,0 |
| Operating temperature min/max (°C) | 5 / 38 |
| Hydraulic connection inlet ⁽¹⁾ | Push-fit, ¼" polytube |
| Hydraulic connection outlet (faucet) | Push-fit, ¼" polytube |

⁽¹⁾ Supplied with installation kit with ½" BSP male/female T-adaptor to inlet plumbing

PERFORMANCES⁽²⁾

| Model | SOF-POU | | |
|---------------------------------------|---------|---|---|
| Stages | 1 | 2 | 3 |
| Service flow (Ltr/min) ⁽²⁾ | 2,0 | | |

⁽²⁾ Varies with inlet pressure and faucet configuration

DIMENSIONS & WEIGHTS

| Model | SOF-POU | | |
|----------------------------|---------|-----|-----|
| Stages | 1 | 2 | 3 |
| Width (mm) ⁽³⁾ | 120 | 240 | 360 |
| Height (mm) ⁽⁴⁾ | 393 | 393 | 393 |
| Depth (mm) | 120 | 120 | 120 |
| Weight (kg) | 1,5 | 2,8 | 4,0 |

⁽³⁾ Allow min. 75 mm clearance at left & right side for installation of tubing to inlet/outlet

⁽⁴⁾ Allow min. 50 mm clearance at bottom side for change-out of twist-lock filter cartridge(s)

FEATURES & BENEFITS

- Quickfit connection
- Pushfit sealed cartridges
- Automatic shut-off
- Premium quality faucet

