



POE sediment filter



softena

A real sense of comfort & performance.

ERIE WATER TREATMENT
Bannerlaan 83E,
B-2280 Grobbendonk - Belgium
T +32 (0)14 28 51 71
infobelgium@eriewatertreatment.com
WWW.ERIE-SOFTENA.COM

MEMBERSHIPS



CERTIFICATIONS



softena

POE sediment filter

SOF-POE-1



SOF-POE-2



TECHNICAL SPECIFICATIONS

Model	SOF-POE-1	SOF-POE-2
Operating pressure min/max (bar)	10,0	10,0
Operating temperature min/max (°C)	5 / 50	5 / 50
Hydraulic connection inlet/outlet	3/4" BSP Male	3/4" BSP Male
Hydraulic connection drain (mm)	30	30
Electrical connection (V/Hz)	N/A	230/50 ⁽¹⁾
Max. power consumption (A)	N/A	0,8

⁽¹⁾ Supplied with 24V transformer

PERFORMANCES

Model	SOF-POE-1	SOF-POE-2
Service flow rate @ 1 bar pressure drop (m ³ /hr)	6,1	6,1
Filter mesh size (µ)	100	100
Nominal backwash flow = flow to drain (Ltr/min)(1)	15	15

⁽¹⁾ Varies with inlet pressure

DIMENSIONS & WEIGHTS

Model	SOF-POE-1
Width (mm)	200
Height (mm)	319
Depth (mm)	96
Weight (kg)	1,8

⁽²⁾ Allow min. 150 mm free space at bottom side for easy installation of drain